

E210 Series

Cost-Effective, Rugged
LTE Routers



WAN, LAN, WI-FI SMART IOT ROUTER WITH EDGE CAPABILITY IN A TINY, INDUSTRIAL FORM FACTOR

Lantronix E210 routers designed with high resiliency, industrial grade, Cellular LTE, M1 or Cat1, WAN, LAN, Wi-Fi, and serial connectivity provide robust connectivity for faultless requirements. E210 is perfect for IoT and enterprise applications, including industrial automation, Industry 4.0, Smart city, smart building application, and transportation connectivity. E210 series routers provide state-of-the-art load balancing, multiple VPN tunneling schemes including IPsec, and cellular/WAN/Wi-Fi failover scheme. Automatic failover functionality ensures Internet connectivity for your applications with minimum connection problems. With dual SIM support, the router can use your application to selectively choose the SIM used for data or easily switch between them based on Quality of Service (QoS).

Centralized Device Management Platform

Monitor, manage, and control your devices from anywhere, at any time, with the ready-to-use software platform web application. The easy-to-use platform provides software-defined automation with zero-touch provisioning across all of your devices and the capture of device telemetry data for event management and analytics.

Protect, Process, and Customize the Edge

Based on Linux frameworks and Lantronix ePack software suite, the E210 routers provide a user-friendly environment to develop your application, leverage the crowd and the community of Linux developers, and more than hundreds of applications supported by our Linux framework.

Reduce your recurring cost and ensure the fastest response time from your device in two ways:

- Store logs for records, store external device data for data logging purposes on E210 SD card, or
- Send to the cloud only what you need by processing the data to the edge

Ultimate stability with load balancing and failover using Dual SIM Operation

Lantronix E210 has an automatic failover functionality that prevents your loss of communication even if you have a connection problem with cellular redundancy by dual SIM support. Switching based on Quality of Service. Program your scripts and conditions of switching.

Security and VPN support

Keep your critical data safe from cyber-attack by using advanced encryption such as AES, SSL/TLS. E210 supports major VPN profiles, including Open VPN, which offers the highest performance, is reliable on high latency connections, and is easy to set up. With a 256-bit encryption protocol, your information is safe. This platform offers improved stability and compatibility for all your devices.


Perfect For:



Industry 4.0



Smart Building &
Smart City



Security



Sales &
Payment

E210 Series Highlights

- Fieldbus protocol conversion: Modbus, DNP3, IEC 104, DLMS, Dual Sim
- Edge programming and processing
- Ultra compact form factor
- Multiple interface
- Industrial-grade
- Compatible with all Lantronix Connectivity Services SIM Cards

 LANTRONIX
Connectivity Services

Hardware

Wi-Fi

- 1T1R Wi-Fi 4; via an RP-SMA antenna connector

Cellular

One- or two-antenna models as:

- 3G E215[G]; LTE-M1 E213G; via an SMA antenna connector
- LTE cat. 1 E214[G]; LTE cat. 4 E218[G]; via two SMA antenna connectors (main and diversity)

I/Os

Two isolated digital I/Os; via the lower row of the same header

- INPUT: 0 V dc ~ 1 V dc → ZERO; 1.4 V ~ 36 V dc → ONE
- OUTPUT: open collector; 100 mA max.; 36 V dc max.

Serial Communication

- RS232 Full implementation; via a 9-pin sub-D header

10/100Base-Ethernet

- One LAN port and one WAN port, user-reconfigurable as second LAN port; via RJ-45 headers fitted with two LEDs

Dual SIM

- Dual SIM / Single standby ("DSSS"); via two mini-SIM held in trays

Location Services

- Concurrent GPS and GLONASS (E215G, E213G); IZat™ gen. 8CpsOne (E214G, E218G); via a dedicated SMA antenna connector

Data Storage

- Via a user-accessible microSD card (not provided)

DDR2 SDRAM

- Doubled to 256 MB

Alternate Data Storage

- 64 MB [resp. 1 GB] of internal Flash memory, arranged in 512- [resp. 2,048-] byte pages, substituted for the standard microSD card holder

MFF SIM(s)

- Combination of (i) 'MFF + mini'; or (ii) 'mini + MFF'; or (iii) 'MFF + MFF' SIMs, substituted for the standard two mini-SIM trays

Physical Description

- Brushed aluminum alloy
- Size: (MM) 92.5 x 57.2 x 22.5
- SSL v3, SSH v2 Client & Server - up to 2048-bit certificates
- Encryption: AES 3DES, RC4
- Authentication: SHA-1, MD5, Base-64 connectors
- Weight: Approx. 150 g
- LED: (i) POWER; blue for (ii) SIM; (iii) Wi-Fi; amber for (iv) Activity; (v) Network; (vi) Signal; red for (vii) ALERT

Temperature & Humidity Ranges

- Operating: -20 °C ~ +60 °C; up to 95% RH
- Storage: -40 °C ~ +85 °C; up to 95% RH

CPU

- MIPS32® 24KEc™ CPU running at 580 MHz
- Built-in 64 KB [resp. 32 KB] instruction [resp. data] cache
- SPI Flash Memory: 32 MB

Power-off Timekeeping

- RTC with an approx. 100-day data retention period; courtesy of a 15 mWh lithium manganese battery (not functional below -20 °C)

Power Consumption (W)

- All figures worst-case (60 °C, 32 V, all subsystems fired on, etc.)
- Idle: 0.96 (E215); 1.10 (E214); 1.10 (E218)
- Standby: 2.31 (E215); 2.63 (E214); 2.63 (E218)
- Communication (Tx max.): 5.54 (E215); 6.18 (E214); 6.18 (E218)

Power

- 8 V dc ~ 32 V dc with SLOW START; via the upper row of a dual row, 4-pin, Micro-Fit™ 3.0 header

Software Suite

Administration And Network Protocols

- Web-based user interface, setup wizard, console log viewer, save / load configuration, NTP, SMS / OTA remote configuration, TR-069-capable

Redundancy

- Web-based user interface, setup wizard, console log viewer, save / load configuration, NTP, SMS / OTA remote configuration, TR-069-capable
- Ethernet, Cellular, Wi-Fi – configurable as failover or load balancing

Resilience

- Network connectivity watchdog (configurable), internal application watchdog

Wi-Fi

- Client or Access point (approx. 40-user), multiple SSID, WEP, WPA, WPA-PSK / WPA2-PSK security modes

Device Management Services

- Lantronix ConsoleFlow™ platform or third-party platforms such as TrinitySMART, Cumulocity, etc

Connectivity Services

- Compatible with all Lantronix Connectivity Services SIM Cards

Performance And Fault Management

- Real time processor load and interface (WAN / LAN / Wi-Fi), traffic analysis, ICMP, trace-route, NS lookup

Routing

- DHCP, static routing, port forwarding, traffic routing, static /dynamic DNS, DNS proxy, NAT, STP

VPN

- PPTP client, L2TP, OpenVPN client / server / passthrough, GRE, IPsec

Security

- Zone-based firewall, VLAN, DMZ, HTTPS local and remote connection, SIM PIN

Industrial Protocols

- MODBUS RTU/TCP to IEC-60870-5-104 converter
- Modbus Master mode
- Modbus RTU to Modbus TCP converter
- Modbus to MQTT / Cumulocity / FTP / Azure / Http, Serial to FTP converter
- IEC-60870-5-101 to IEC-60870-5-104 converter
- Modbus to DNP3 converter
- I/O to Modbus converter
- I/O to IEC 104
- I/O toggling through SMS

Warranty

- One Year Limited

Certifications

- E214 RCM, NBTC, CE, SIRIM
- E214G FCC, Verizon Wireless, ISED, PTCRB, AT&T Wireless

Accessories

Snap CAP™:

SC485, a 9-pin male sub-D plug that 'snappily' converts any E210 unit into an isolated, half- or full-duplex (user-selectable via a slide switch) RS-485 unit via a 5-pin, 3.5 mm pitch, COMBICON header

Visit www.lantronix.com/products/e210-series-routers/ for a full listing of available accessories.

Product Variants

Part Number	Description
E214F002S	Router E214 EMEA Malaysia - LTE cat. 1 band 28, 20, 8, 3, 1, 7 - 3G FB 8,1 - 2G FB band 8, 3 - 2 Ethernet, Dual SIM, RS-232 port, Wi-Fi, SD card, 2 I/O - Epack
E214F00CS	Router E214 China, Indonesia, India - LTE cat. 1 band 5, 8, 3, 1; TDD 40, 41 - 3G FB 8,1 - 2G FB band 8, 3 - 2 Ethernet, Dual SIM, RS-232 port, Wi-Fi, SD card, 2 I/O - Epack
E214G000S	Router E214 AT&T, T-Mobile - LTE cat. 1 band 12, 5, 4, 2 - 3G FB 5, 4, 2 - 2 Ethernet, Dual SIM, RS-232 port, Wi-Fi, SD card, 2 I/O - Epack
E214G001S	Router E214 Verizon - LTE cat. 1 band 13, 14 - 2 Ethernet, Dual SIM, RS-232 port, Wi-Fi, SD card, 2 I/O - Epack
E218F004S	Router E218 Brazil ANZ Thailand Malaysia Singapore - LTE Cat4 band 28, 5, 8, 3, 1 - 3G FB 5, 8, 1 2G FB 8, 3 - 2 Ethernet, Dual SIM, RS-232 port, Wi-Fi, SD card, 2 I/O - Epack